



<i>Name:</i>	_ <u>Tractor</u>
Address:	Make:
<i>City, St, Zip:</i>	Model:
E-Mail:	_ Weight Class:

Please select one weight class from the list below.

<u>Antique</u>	Improved Farm Stock	<u>Open</u>
6,500	3,750	9,000
	5,000	
<u>Classic</u>	7,000	
9,000	9,000	
	10,000	Modified
Hobby Stock	12,000	6,500
11,000	16,500	
	22,000	

- Entry Fee:
 - If per-registered \$25.00 Includes Driver and one pit person. You do not need to pay when you pre-register. You can pay when you arrive at the gate.
 - Drive up entries \$40.00
- Pre-register by calling, texting, or e-mailing Mark Emslander, or the Fair Grounds Office. Drivers should be pre-registered before Wed, Aug. 3rd, 10:00 PM.
- Drivers and tractors must be checked at the Fair Grounds by 6:30 PM.

I understand the entry fee is kept by the fair association and is used toward prize money. I understand that the sponsors and administrators of the contest are not responsible for any accidents, injury, damage or mechanical breakage if it should occur.

In consideration of your accepting the entry, I here-by for myself, my heirs, executors, and administrators, release and forever discharge the sponsors and administrators, their agents, servants and all the persons connected with these competitions of and from any loss, damage, or injury sustained by me or my equipment during this competition.

I also understand that all tractors are subject to weight checks for proper weight classifications and have read and understand the rules.

Please mail or contact:

Mark Emslander 5587 Hawk Ridge Rd. Grasston, MN 55030 (320) 224-4251 markemslander@gmail.com Pine County Fairgrounds (320) 629-3408 www.pinecountyfair.com

Nick Raudabaugh 23622 Russell Rd Pine City, MN 55063 (320) 224-4784 deerecreekfarms@gmail.com

PINE COUNTY FAIR TRACTOR PULL RULES

- 1. All engine fans must be shrouded steel 1/16" or thicker. All transmissions and clutch housings covered. All turbos not under hood must be completely shrouded except for an inlet and exhaust pipe 1/16" or thicker.
- 2. No parts of the tractor may interfere with the sled during pull. Front weights and support frame-Maximum 11' from center of rear axle. All weights must be safely secured to the tractor and must not be on the 3-point arms.
- 3. Only one fuel per tractor.
- 4. All ignition engines must have a kill switch in working order within reach of the driver.
- 5. All exhaust must be factory or discharged vertically upward. No rain caps or curved pipes on hobby or open.
- 6. All classes will use standard drawbar rules. Minimum drawbar length of 18" from the center of the rear wheel to the point of hook measured horizontally. Drawbar must be stationary in all directions. Maximum drawbar height is 20" from hitching point parallel to the ground. Pull point may not be more than 1 ¹/₂" from the back edge of the hitching point. No bracing drawbar to 3-point or top link.
- 7. Operator must remain seated during the pull and have complete control of the tractor at all times. All tractors must have working rear brakes.
- 8. Tractors may down shift during the pull provided the forward motion of the sled is continued. The use of torque amplifiers and power shifts are allowed.
- 9. No consumption of alcoholic beverages or drugs in the pit area before, or during the contest. If any one judge believes any driver to be a potential safety hazard, that driver will be disqualified with no refund of entry fee.
- 10. Tractor and skid must remain within the boundaries of the course.
- 11. Contest is to be governed by judges with all decisions final. Judges have the right to stop and disqualify at any time. Entry fees will not be refunded.
- 12. Any parts of equipment falling off the tractor will disqualify the pull.
- 13. One pull per tractor per weight class. No first puller re-pull option.
- 14. Protests must be made from a puller from the same class, and before the end of the following class. The protester must submit \$50.00 to the judges along with the specific rule infraction and driver being protested. Both tractors will be checked. If the protest is invalid, the money is forfeited, if valid, the driver protested must pay the protest fee. Judges decisions are final.
- 15. All underage drivers must have parent's written permission. Parents assume all responsibility, subject to judge's decision.
- 16. Sportsmanship Rule: Unsportsman like conduct will not be tolerated and will result a year and a day suspension.

ANTIQUE - 6500 lb. (1950 or older)

Stock RPM's, Tire Chart Specs, factory stock motor, carburetor and drive train for that make and model. No Block Spacers.

<u>CLASSIC</u> - 9000 lb. (1958 or older)

Tire Chart Specs, Factory stock motor, carburetor and drive train for that make and model, No Block Spacers

IMPROVED FARM STOCK - 3750, 5000, 7000, 9000 (NO SPEED LIMIT)

Factory appearing or stock replacement block, carburetor or pump, front end and drive train for that make and model. Factory stock turbo allowed. 3,500 to 5,000 maximum tire size- 16.9-38, 7,000 to 9,000, tire size max. 18.4-38

IMPROVED FARM STOCK - 10000, 12000, 16500, 22000 (NO SPEED LIMIT)

Factory appearing or stock replacement block, carburetor or pump, front end and drive train for that make and model. Factory turbo or M&W T04 (Add-on) must hook up to factory intake and exhaust with no modifications. Must have fenders, floor plate and factory wide front end.

HOBBY STOCK

Power block allowed. Wheelie bars required for safety. Scatter blanket required around clutch & flywheel. Breakaway switch required. Dead man throttle required. Gas, propane, or diesel fuel only. No nitrous or oxidizers, One fuel only per tractor. Side shields must be removable. Wide front minimum of 60" wide. One single barrel updraft carburetor allowed, no intake manifold limit, carburetor must be below intake ports on head. 3X4 Turbos allowed. Fuel shut off between pump and fuel filters.

OPEN CLASS / MODIFIED

Must have wheelie bars, Breakaway switch and second emergency shut off within reach of driver mandatory. Factory appearing block, Scatter blanket or ¹/₄" steel plate required around clutch & flywheel. Exhaust pipe must be cross-bolted, front damper covered. Roll-over protection, MUST support the weight of the tractor. Helmet and full fire suit MANDATORY.